



**WACKER  
NEUSON**  
*all it takes!*

# SM60

## Tracked Mini Loader



### Do more with less

The SM60 is comfortable for operators, while maintaining its trim and compact profile, utilising its wide spring suspension for both enhanced comfort as well as enhanced stability. In addition, the SM60 utilises a petrol motor for DIY home owners and landscape contractors who use petrol to power their equipment. With a purpose designed lift capacity and high hinge pin, the SM60 excels at loading onto high sided trucks and dumpsters.



#### Compact design

The overall machine width of 902mm without bucket fits through doorways, gates and other tight spaces. The overall narrow width allows the machine to access urban areas and smaller yards while the light weight (1,252 kg) makes it easy to transport.



#### Industry leading safety features

Operator presence pedal and hydraulic function lockouts prevent accidental movement of lift arm and drive functions.

#### All day comfort

Large spring-suspended operator platform provides comfort and a stable base for the operator. Fine tuned forward angled joysticks, position the operator's hands in a neutral position to reduce fatigue. Plush padding provides comfort and stability. Additional features include a cup holder, 12v charging port and storage compartment.



## Professional grade undercarriage

Durable undercarriage reduces maintenance costs and Total Cost of Ownership through innovative design and quick maintenance. Sealed idlers and triple flanged rollers provide added surface area and engagement to reduce wear and de-tracking.



## Premium performance

The SM60 is powered by a 26.5 horsepower Kohler petrol engine providing high torque and a flat power curve to enhance productivity through fast cycling times and expectational pushing power. 49 lpm of auxiliary hydraulic flow is available to power a wide variety of money saving attachments.

## Built tough

Internal fuel and hydraulic oil tanks are protected from damage. Angled unibody chassis design sheds debris, reducing wear & tear.



## Technical Information

	Units	SM60
<b>Hydraulic</b>		
Flow rate	l/min	46
Auxilliary relief pressure	bar	210
<b>Mechanical – Output Details</b>		
Ground pressure (standard track)	bar	0.3
Travel speed	km/h	6.3
<b>Mechanical Details</b>		
Overall length without bucket	mm	1,920
Overall length with bucket	mm	2,501
Overall width without bucket	mm	902
Height	mm	1,392
Bucket hinge pin height	mm	1,920
Bucket roll back at ground	°	25
Bucket roll back at max. height	°	92
Angle of departure	°	23
Bucket dump height at max. height	mm	2,635

	Units	SM60
Bucket dump angle at max. height	°	37
Operating weight	kg	1,252
Track width	mm	178
Ground clearance	mm	173
Length of track on ground	mm	826
Dump reach at max. height	mm	684
<b>Engine</b>		
Maximum torque	Nm	85
<b>Operating Fluids</b>		
Fuel tank capacity	l	53
<b>Chassis</b>		
Tip Load	kg	780
Rated operating capacity at 50% tip load	kg	390
Rated operating capacity at 35% tip load	kg	273

The images, equipment and data shown may differ from the range of products currently available in your country. Optional equipment may be shown under certain circumstances subject to a surcharge in the price. The right to make any changes is reserved.

[www.wackerneuson.com](http://www.wackerneuson.com)